

BS SERIES - SINK MOUNT FOOD WASTE DISPOSERS

disperator®

m
MEIKO



Disperator food waste disposers are designed for the immediate and hygienic removal of food waste from preparation and cooking areas.

Designed for installation within a standard sink bowl by means of a nipple attachment welded into the waste outlet. The stainless steel flange that is provided as an integral part of the food waste disposer is then threaded onto the attachment. The narrow 80mm diameter of the disposer inlet prevents access to the rotating grinding unit during operation.

The grinding assembly itself is made from specially cast steel alloy, and is provided with uniquely designed shaft seals and an IP55 rated motor for long and trouble free operation. The disposer inlet, nipple attachment and flange, and grinding motor assembly are manufactured from high grade type EN1.4301 stainless steel for ease of cleaning and for durability.

Provided as standard with the **BS sink mount disposer** will be :-

- IP67 rated safety switch
- IP65 rated solenoid valve
- In-line water strainer
- IP55 rate start-stop control unit
- 2m motor connection cable
- Cutlery trap and feeder
- Grinding unit jam release wrench



START-STOP UNIT INCLUDED



LINE STRAINER INCLUDED



CUTLERY TRAP & FEEDER INCLUDED



SOLENOID VALVE WITH COIL INCLUDED



JAM RELEASE WRENCH INCLUDED

Model	510-BS	515-BS
Capacity	300kg/hr	400kg/hr
Meals	500/day	1000/day
Motor	0.75kW	1.1kW
Water*	14lt/min	16lt/min

**Water consumption will reduce considerably if the macerated food waste is transported short distances and there are limited bends within the transport pipe system.*



Disperator food waste disposers have been manufactured in Sweden since 1946 and have an outstanding reputation for engineering quality across a wide and varied range of catering operations, from traditional hotel & catering outlets, to cruise liners and ferries, and more recently as an integral part of compact vacuum food waste extraction systems.