

MC SERIES - FREESTANDING FOOD WASTE DISPOSERS

disperator®

m
MEIKO



Disperator food waste disposers are designed for the immediate and hygienic removal of food waste from preparation and cooking areas.

The **MC** models allow the continuous feeding of food waste into the disposer. The sloping safety cover is fitted with a safety switch that prevents access to the rotating grinding unit during operation, and the appliance is delivered ready to be connected to the on-site isolated services.

The grinding assembly itself is made from specially cast steel alloy, and is provided with uniquely designed shaft seals and an IP55 rated motor for long and trouble free operation. The disposer inlet, safety cover guard, and grinding motor assembly are all manufactured from high grade type EN1.4301 stainless steel for ease of cleaning and for durability.

Provided as standard with the **MC bench mount disposer** will be :-

- IP67 rated safety switch
- Class 'A' air gap kit
- IP65 rated solenoid valve
- In-line water strainer
- Set of 4 adjustable legs
- 2m motor connection cable
- Grinding unit jam release wrench
- Cutlery saving magnet



LINE STRAINER INCLUDED



CLASS 'A' AIR GAP INCLUDED



SOLENOID VALVE WITH COIL INCLUDED



JAM RELEASE WRENCH INCLUDED

Model	510-MC	515-MC	520-MC	530-MC	550-MC
Capacity	300kg/hr	400kg/hr	500kg/hr	700kg/hr	850kg/hr
Meals	500/day	1000/day	1250/day	1500/day	2000/day
Motor	0.75kW	1.1kW	1.5kW	2.2kW	4.0kW
Water*	14lt/min	16lt/min	18lt/min	22lt/min	27lt/min

*Water consumption will reduce considerably if the macerated food waste is transported short distances and there are limited bends within the transport pipe system.



Disperator food waste disposers have been manufactured in Sweden since 1946 and have an outstanding reputation for engineering quality across a wide and varied range of catering operations, from traditional hotel & catering outlets, to cruise liners and ferries, and more recently as an integral part of compact vacuum food waste extraction systems.